

ねじなし	外径(mm)	厚さ(mm)	1束
E19	19.1	1.2	10
E25	25.4	1.2	10
E31	31.8	1.4	7
E39	38.1	1.4	5
E51	50.8	1.4	3
E63	63.5	1.6	1
E75	76.2	1.8	1

薄鋼	外径(mm)	厚さ(mm)	1束
C19	19.1	1.6	10
C25	25.4	1.6	10
C31	31.8	1.6	7
C39	38.1	1.6	5
C51	50.8	1.6	3
C63	63.5	2	1
C75	76.2	2	1

厚鋼	外径(mm)	厚さ(mm)	1束
G16	21.0	2.3	10
G22	26.5	2.3	7
G28	33.3	2.5	5
G36	41.9	2.5	3
G42	47.8	2.5	3
G54	59.6	2.8	1
G70	75.2	2.8	1
G82	87.9	2.8	1
G92	100.7	3.5	1
G104	113.4	3.5	1

VE管	外径(φmm)	内径(φmm)	1束
14	18	14	20
16	22	18	30
22	26	22	30
28	34	28	20
36	42	35	10
42	48	40	5
54	60	51	5
70	76	67	3
82	89	77	3

CD管	外径(mm)	内径(mm)	M/巻
14	φ19	φ14	50
16	φ21	φ16	50
22	φ27.5	φ22	50
28	φ34	φ28	30
36	φ42	φ36	30
42	φ48	φ42	30
54	φ50	φ54	30

PF管	外径(mm)	内径(mm)	M/巻
14	φ21.5	φ14	50
16	φ23	φ16	50
22	φ30.5	φ22	50
28	φ36.5	φ28	30
36	φ45.5	φ36	30
42	φ52	φ42	30
54	φ64.5	φ54	30

ミライFEP	外径(mm)	内径(mm)	適合ケーブル外径
20	30.5	20	~14mm
30	41	30	~20
40	55	40	~26.5
50	66	50	~33
65	86	65	~43
80	103	80	~53
100	131	100	~66.5
125	163	125	~83
150	194	150	~100
200	257	200	~133

VP管	外径(mm)	厚さ(mm)
13	18	2.5
16	22	3
20	26	3
25	32	3.5
30	38	3.5
40	48	4
50	60	4.5
65	76	4.5
75	89	5.9

①三相誘導電動機 (50m以内)					
定格出力		規約電流(A)		電線の太さ(mm ²)	
KW	馬力	200V	400V	200V	400V
0.2	0.25	1.8	0.9	0.75	0.75
0.4	0.5	3.2	1.6	0.75	0.75
0.75	1	4.8	2.4	0.75	0.75
1.5	2	8.0	4.0	1.25	0.75
2.2	3	11.1	5.5	2.0	1.25
3.7	5	17.4	8.7	3.5	2.0
5.5	7.5	26	13	5.5	3.5
7.5	10	34	17	8	3.5
11	15	48	24	14	5.5
15	20	65	32	22	8
18.5	25	79	39	30	14
22	30	93	46	38	22
30	40	125	62	60	22
37	50	160	80	80	38
45	60	190	95	125	50
55	75	230	115	200	60
75	100	310	155	325	100
90	120	360	180	400	125
110	145	440	220	600	200
132	175	500	250	800	250

3心キャブタイヤケーブルを使用した場合

②単相電動機 (50m以内)					
定格出力		規約電流(A)		電線の太さ(mm ²)	
KW	馬力	100V	200V	100V	200V
0.035	1/22	2.2	1.1	0.75	0.75
0.065	1/12	3.0	1.5	0.75	0.75
0.1	1/8	5.1	2.5	0.75	0.75
0.125	1/6	5.6	2.8	0.75	0.75
0.15	1/5	6.0	3.0	0.75	0.75
0.2	1/4	7.2	3.6	0.75	0.75
0.25	1/3	8.4	4.2	0.75	0.75
0.4	1/2	11.1	5.5	1.25	0.75
0.55	3/4	14.0	7.0	2.0	0.75
0.75	1	17.7	8.8	3.5	1.25
1.1	1.5	23.0	11.5	3.5	1.25
1.5	2	28.0	14.0	5.5	2
2.2	3	36.0	18.0	8	3.5
3.7	5	52.0	26.0	14	5.5
5.5	7 1/2	67.0	33.5	30	8
7.5	10	83.0	41.5	38	14

2心キャブタイヤケーブルを使用した場合